

PRODUCT DATA SHEET

Lubricants – Industrial

Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, **HYUNDAI XTeer** created by Hyundai's built-up technology will open the new world of Industrial lubricants.

XTeer COMP-P VG 68, 100

Description

XTeer COMP-P is an extraordinary Compressor Oil. It is formulated with excellent quality base oil technology and a high technology additive system that assures exceptional equipment protection and reliability for compressors operating. It is especially designed to provide excellent wear protection and outstanding resistance to oxidation and thermal. Furthermore, it shows the ability to help reduce maintenance costs through minimizing equipment problems and downstream deposits and carryover.

Application

Recommended for continuous high temperature operation

- ✧ Specifically recommended for reciprocating air compressor
- ✧ Units operating under severe conditions

Features / Benefits

- ✧ Oxidation Stability
- ✧ Low Evaporation Loss
- ✧ Antifoam Properties
- ✧ Rust Protection



Remarks

XTeer COMP-P meets or exceeds the requirements of

- ✧ SIEMENS TLV 9013 04
- ✧ SIEMENS TLV 9013 05
- ✧ ALSTOM HTGD 90117 W0001
- ✧ GENERAL ELECTRIC GEK-32568J
- ✧ DIN 51515 Part 1, 2

XTeer COMP-P VG		68	100
Density (15°C, kg/m ³)		820	876
Viscosity	40°C	72.99	108.4
	100°C	9.47	12.26
Viscosity Index		107	104
Flash Point (°C)		240	246
Pour Point (°C)		-30	-35