

PRODUCT DATA SHEET

Lubricants – Industrial

Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, **HYUNDAI XTeer** created by Hyundai's built-up technology will open the new world of Industrial lubricants.

XTeer Turbine Oil 32, 46, 100

Description

XTeer Turbine Oil is a turbine oil made of high quality base oil and additives that is suitable for bearings of steam turbines, gas turbines and hydraulic turbines.

Application

- ✧ Steam or gas turbines for industries / power generator / ships
- ✧ Bearings of all kinds of compressors
(Especially centrifugal compressor)
- ✧ Decelerators and governor controls
- ✧ Bearings of power plant turbines,
Decelerators and generators and
Governor controls



Features / Benefits

- ✧ Protection against oxidation
- ✧ Protection against rust and corrosion

XTeer Turbine VG		32	46	100
Density (15°C, kg/m ³)		852.2	857.1	866.5
Viscosity	40°C	31.53	43.63	96.6
	100°C	5.41	6.72	11.2
Viscosity Index		105	107	102
Flash Point (°C)		222	230	274
Pour Point (°C)		-40	-32.5	-22.5

Remarks

XTeer Turbine Oil meets or exceeds the requirements of

- ✧ Siemens TLV 9013 04
- ✧ Alstom HTGD 90117
- ✧ General Electric GEK-32568F
- ✧ Solar Turbines ES 9-224
- ✧ DIN 51515